

TECHNICAL SHEET

Article: B0993A PERSEUS

Norm: EN ISO 20345:2022

Safety Class: S3L FO SR

Sole	S29 BLACK
Weight, size 42:	560 gr
Footwear height:	132 mm
Width:	12
Construction / Sole:	STROBEL; single density AirTech injected outsole
Anti-perforation insert	Fresh'n Flex ballistic fabric
Insole:	
Footbed supplied:	B07
Other usable Footbeds (certified):	Dry'n Air Gel; Dry'n Air Omnia; Dry'n Air Scan&Fit Omnia; Secosol; Secosol Dynamic



Entire footwear: protections

Component	Description	Value	Minimum Requirement	Norm
SlimCap toe-cap	Impact Resistance (200J)	16,0 mm	≥ 14,0 mm	5.3.2.3
	Compression Resistance (15 kN)	17,5 mm	≥ 14,0 mm	5.3.2.4
Outsole (SR)	Slip Resistance 20345:2022			
	•Ceramic + Det. - Hill	0,46	≥ 0,31	5.3.5.2
	•Ceramic + Det. + Tip	0,40	≥ 0,36	5.3.5.2
	•Ceramic + Glycerin (SR) - Hill	0,22	≥ 0,19	6.2.10.1
Outsole (SRC)	Slip resistance 20345:2011			
	•SRA – Hill (angle of 7°)	0,45	≥ 0,28	5.3.5.2
	•SRA – sole (full sole)	0,42	≥ 0,32	5.3.5.2
	•SRB – Hill (angle of 7°)	0,23	≥ 0,13	5.3.5.3
Energy absorption (E)	•SRB – Sole (Full sole)	0,24	≥ 0,18	5.3.5.3
	Shock-absorption in the heel region	32 J	≥ 20 J	6.2.4

Upper

Materials	Description	Value	Minimum Requirement	Norm
Split leather	Tear resistance	188 N	≥ 120 N	5.4.3
	Traction resistance	19 N/mm ²	≥ 15 N/mm ²	5.4.4
	Water steam permeability	4,2 mg/cm ² h	≥ 0,8 mg/cm ² h	5.4.6
	Water steam coefficient	42,4 mg/cm ²	≥ 15mg/cm ²	5.4.6
	Chromium VI content (if leather)	Not detectable	Not detectable	6.11
	Water passed	0,0 g	≤ 0,2 g	6.3
	Water absorption	14 %	≤ 30%	6.3

Lining

Materials	Description	Value	Minimum Requirement	Norm
Hi-tech 3D fabric	Tear resistance	47 N	≥ 15 N	5.5.1
	Abrasion resistance	• No dry hole	No holes before 51,200 cycles	5.5.2
		• No hole in humid environment	No holes before 25,600 cycles	5.5.2
	Water steam permeability	21,1 mg/cm ² h	≥ 2,0 mg/cm ² h	5.5.3
Chromium VI content (if leather)	N/A	Not detectable	5.5.5	

Sole

Materials	Description	Value	Minimum Requirement	Norm
Single density AirTech outsole	Crampon height	4,6 mm	≥ 2,5 mm	5.8.1.3
	Tear resistance	10,0 kN/m	≥ 5 kN/m	5.8.2
	Abrasion resistance	172 mm ³	≤ 250 mm ³	5.8.3
	Flexural strength after 30,000 cycles	2,2 mm	≤ 4,0 mm	5.8.4
	Flexural strength after 150,000 cycles (hydrolysis)	2,5 mm	≤ 6,0 mm	5.8.5
	Tread-midsole detachment	N/A	> 4 N/mm; ≥ 3 N/mm with sole tear*	5.8.6
	Hydrocarbon resistance FO (volume change)	4 %	≤ 12%	6.4.2

Issued by: Innovation Director Ing. Cataldo De Luca

Signature



The content of this technical sheet is copyright of BASE PROTECTION Unipersonale Srl. Reproduction, even partial, of texts and / or images presented here is expressly forbidden.

Technical sheet subject to revision at the same time as the certificate is issued. Typographical errors excepted. BASE PROTECTION reserves the right to modify the content of the technical sheet.